

#233 Grade Natural Reinforced Tape

Description: Fiberglass reinforced natural kraft carton sealing tape, manufactured with water activated adhesive.

Construction (per 3000 square feet):

| | |
|-------------------------|---|
| Top Ply: | 20.0 Lb. Natural Kraft Paper (virgin fibers) |
| Bottom Ply: | 23.0 Lb. Natural Kraft Paper (virgin fibers) |
| Laminating Adhesive: | 13.0 Lb. High Melt Index Polypropylene Based Co-Polymer |
| Remoistenable Adhesive: | 14.0 Lb. Chemically Grafted Starch Based Co-Polymer Adhesive Designated as #911. |
| MD Reinforcement: | 1.58 Lb. (1-1-1-1) 110 Fiberglass (per 70mm), 5/8" spacing |
| CD Reinforcement: | 1.28 Lb. (1-1-1) 150 Fiberglass, 1-1/4" spacing, 37 degree angle |
| Total Basis Weight: | 72.9 Lb. |

Physical Properties:

| | |
|------------------------|-----|
| Caliper (mils): | 5.5 |
| MD Tensile (Lbs./in.): | 67 |
| CD Tensile (Lbs./in.): | 26 |

Product Application:

Recommend using on light weight cartons up to 20 pounds.

Standard Sizes Available:

70mm by 375 feet (8 rolls per carton)

70mm by 450 feet (10 rolls per carton)