

#250 Grade Natural Reinforced Tape

Description: Fiberglass reinforced natural kraft carton sealing tape, manufactured with water activated adhesive.

Construction (per 3000 square feet):

Top Ply: 23.0 Lb. Natural Kraft Paper (virgin fibers)
Bottom Ply: 23.0 Lb. Natural Kraft Paper (virgin fibers)
Laminating Adhesive: 14.5 Lb. High Melt Index Polypropylene Based Co-Polymer
Remoistenable Adhesive: 15.0 Lb. Chemically Grafted Starch Based Co-Polymer Adhesive
Designated as #911.
MD Reinforcement: 3.20 Lb. (1-1-1-1-1) 75 Fiberglass (per 3 inch), 1/2" spacing
CD Reinforcement: 1.48 Lb. (1-1-1) 150 Fiberglass, 1-1/2" spacing, 45 degree angle
Total Basis Weight: 80.2 Lb.

Physical Properties:

Caliper (mils): 6.3
MD Tensile (Lbs./in.): 75
CD Tensile (Lbs./in.): 26

Product Application:

Recommend using on average cartons up to 40 pounds.

Standard Sizes Available:

3 inch by 375 feet (8 rls per carton) • 3 inch by 1000 feet (6 rls per carton) • 3 inch by 450 feet (10 rls per carton)
3 inch by 600 feet (5 rolls per carton) • 2.5 inch by 450 feet (12 rolls per carton)

#250 Grade SnowWhite Reinforced Tape

Description: Fiberglass reinforced snowwhite kraft carton sealing tape, manufactured with water activated adhesive.

Construction (per 3000 square feet):

Top Ply: 25.0 Lb. White Kraft Paper (virgin fibers)
Bottom Ply: 23.0 Lb. Natural Kraft Paper (virgin fibers)
Laminating Adhesive: 14.5 Lb. High Melt Index Polypropylene Based Co-Polymer
Remoistenable Adhesive: 15.0 Lb. Chemically Grafted Starch Based Co-Polymer Adhesive
Designated as #911.
MD Reinforcement: 3.20 Lb. (1-1-1-1-1) 75 Fiberglass (per 3 inch), 1/2" spacing
CD Reinforcement: 1.48 Lb. (1-1-1) 150 Fiberglass, 1-1/2" spacing, 45 degree angle
Total Basis Weight: 82.2 Lb.

Physical Properties:

Caliper (mils): 6.4
MD Tensile (Lbs./in.): 69
CD Tensile (Lbs./in.): 26

Product Application:

Recommend using on average cartons up to 30 pounds.

Standard Sizes Available:

3 inch by 375 feet (8 rls per carton) • 3 inch by 1000 feet (6 rls per carton) • 3 inch by 450 feet (10 rls per carton)
3 inch by 600 feet (5 rolls per carton) • 2.5 inch by 450 feet (12 rolls per carton)